

Jordspyd i henhold til NEK:2018 Tabell 54A.

For Jording i løsmasser benyttes minimum 14 mm spyd med 250µm elektrolytisk Cu-belegg.

El nr.	Produkt	Beskrivelse
1263105	Jordspyd	Konisk 1000 x 14,2 mm 250 µm CU belegg
1263106	Jordspyd	Konisk 1500 x 14,2 mm 250 µm CU belegg
1263107	Skjøtehylse	14,2 mm konisk
1263108	Topphylse	14,2 mm konisk m/25 mm ² PN
1263109	Topphylse	14,2 mm konisk m/50 mm ² PN
1263110	Slagstykke	For neddriving av 14,2 mm spyd
1263112	Jordingsklemme	For 1/2" - 5/8" spyd
1263113	Spiss	For neddriving av 14,2 mm spyd
1263115	Jordspyd, gjenget	1,5 m lengde, Ø 5/8" 250 µm CU belegg
1263116	Jordspyd, gjenget	1,8 m lengde, Ø 5/8" 250 µm CU belegg
1263117	Skjøtehylse	Ø 5/8" Gjenget
1263118	Anslagsbolt	Ø 5/8" Gjenget
1262990	Jordplate 1x500x1000 mm	



El.nr. 1263106



El.nr. 1263107



El.nr. 1263108



El.nr. 1263109



El.nr. 1263110



El.nr. 1263112



El.nr. 1263113




El.nr. 1263115/1263116



El.nr. 1263117



El.nr. 1263118



El.nr. 1262990